



PCB LAYOUT/TOP VIEW

**Electrical:**

- 1.Voltage Rating:125 Vac Rms.
- 2.Current Rating:1.5 Amp.
- 3.Contact Resistance:40 Milliohms Max.
- 4.Insulation Resistance:1000 Megohms Min @500 Vdc.
- 5.Dielectric Strength:1000 Vac Rms 60Hz, 1Min.

**Mechanical:**

- 1.Operating:750 Cycles Min.

**Environmental:**

- 1.Storage:-40°C To +85°C.
  - 2.Operation:-20°C To +75°C.
  - 3.IR Reflow Soldering Temperature:255°C To 265°C(5~10 Seconds).
- Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

**MATERIALS:**

- PLASTIC HOUSING: HIGH TEMP THERMOPLASTIC  
FLAMMABILITY RATING UL 94V-0.
- CONTACTS: PHOSPHOR BRONZE
- PLATING: GOLD PLATING OVER NICKEL IN CONTACT.  
TIN PLATING OVER NICKEL IN SOLDER AREA.
- SOLDER PAD: BRASS WITH TIN PLATING OVER NICKEL.

LINK-PP INT'L TECHNOLOGY CO., LIMITED

UNIT: mm SCALE: 3/1 SHEET: 1 of 1

TITLE:

TOP ENTRY PCB SMT JACK  
(無断差6P4C)

DRAWN BY

Alan J0425

APPROVED BY

Alan J0425

General Tolerance

DRAW NO:

LPJE22NNL

REV.

A

REV.	DESCRIPTION	DATE